



UHD VARIFOCAL VANDALPROOF DOME SMD IR IU MC4212V



MAIN FEATURES :

- 1 / 2, 9" SONY CMOS SENSOR
- 4 IN 1 : AHD / TVI / CVI / CVBS OUTPUT
 - 1080P RESOLUTION
- SUPPORT OSD & COAXIAL CONTROL
 - 2D & 3D DNR, BLC, D-WDR
 - LENS 2.8-12MM



IU-MC4212V	
Camera	
Image Sensor	1/2.9" SONY CMOS Sensor
Signal System	NTSC/PAL
Effective Pixels	1920(H) x 1080(V)
Electronic Shutter	AUTO/ 1/50 (1/60) -1/50,000sec
Synchronization	External
Min. Illumination	0.01Lux
Video Frame Rate	PAL/NTSC:25/30fps
Video Output	AHD / TVI / CVI / CVBS
Camera Features	
S/N Ratio	>41dB
Noise Reduction	2D&3D DNR
Day&Night	Color / B&W/ AUTO / EXT
White Balance	Auto / Manual/Indoor/Outdoor
OSD	English / Chinese / German / French / Italian / Spanish / Polish / Russian / Portuguese / Dutch / Turkish
AGC	13 (0~15)
IR LED	14μX24pcs SMD LED
IR Range	up to 30m
Lens	
Focal Length	2.8-12mm Manual Zoom lens
Angle of View	H: 100° ~ 32°
Lens Type	Fixed Iris
Mount Type	Φ14 & Metal Housing
General	
IP Rating	IP66
Power Supply	DC12V(+/-10%)
Power Consumption	IR OFF:77mA / IR ON:430mA
Working Temperature / Humidity	—20~+50°C RH95% MAX
Dimensions(W×D×H)	Φ 140X105 (H) mm
Weight	690g